# EASY DUNKER SAFETY RULES

- 1. Keep EASY DUNKER away from electricity.
- 2. Periodically, check tank and trailer frame for sharp edges.
- 3. Keep water level filled to at least 8" from top of tank.
- 4. Only one person at a time allowed on the seat or in the tank.
- 5. Keep all non-swimmers and anyone less than 5' tall out of tank.
- 6. To keep from slipping, always wear tennis shoes.
- 7. Advise dunkee to move towards the front of the tank when coming up out of the water to avoid hitting head on the seat.
- 8. When tank is unattended, always drain water.
- 9. Use tennis balls ONLY! Never use baseballs or other hard balls.
- 10. Never stand on seat.
- 11. When sitting on the seat, keep hands on knees and sit forward.
- 12. Do not hit target with hands.
- 13. Do not operate EASY DUNKER during a storm.
- 14. When towing *EASY DUNKER*, tie a second safety rope around metal frame.
- 15. When towing EASY DUNKER, always use a safety chain. Check brake lights and turn signals.

## EASY DUNKER

### Instructions

#### TO TOW:

- 1. Fold wing in against the side of the unit and securely tie off. Then slowly tilt tank back onto its wheels. Place scat in its "up" position and lock.
- 2. Insert hitch tongue and use both pins to secure it.
- 3. Attach trailer to vehicle. [A 1 7/8" trailer ball is required. (2" hitches available upon request.)] Put pin or bolt through hitch release lever and secure. Attach safety chain to vehicle.
- 4. Hook up lights to tow vehicle, and be sure to test the turn signals and brake lights before towing.
- 5. Place target, target arm, and tennis balls safely in tow vehicle.

#### SET UP

- 1. Select a level area for set up.
- 2. Unhook trailer and lights from tow vehicle and roll to set up area. (NOTE: Trailer and tank are one unit, do not try to separate!)
- 3. Raise tongue end of trailer and remove hitch pins from tongue bar. Slide tongue bar out and replace pins in bar.
- 4. Slowly lift up and set tank upright. (Be careful not to drop tank onto its bottom.)
- 5. Untic rope holding the wing against the tank. Swing wing out into position. It will be necessary to block the bottom of the wing so the wind does not move it as this will cause the target arm to bend.
- 6. Check drain plug to make sure it is tight and then fill tank to the top with water (approx. 500 gallons).
- 7. Place the flattened end of the arm into the trigger mechanism (behind the vice grip handle). Put the other end trough the square tubing on the wing and through the hole in the canvas. Make sure the arm drops into the slot on the side of the frame. Insert the target into the end of the arm so the pin holes line up. Insert the clip pin.
- 8. Place one hand on the front of the seat and push down. With the other hand "test" the target to see that it works properly. (Using the adjustment at the bottom of the vice grip you can adjust the amount of force required to release the seat.)

#### 9. REVIEW SAFETY RULES!!

{OVER}

#### **OPERATION**

- 1. Check to see that seat is properly locked and vice grip is released when the target is pressed. Be sure to show this operation to the person who will be on the tank as they will need to know how to reset the seat and vice grips each time it is released, before they get back onto the seat. Please remind the dunkee to keep their hands on their knees and sit forward on the seat.
- 2. Use ONLY tennis balls with the EASY DUNKER any other type can damage the tank and possibly cause injuries.
- Monitor water level to keep it full.

#### TAKE DOWN

- 1. As soon as you are finished using the dunker, remove the drain plug and let the tank empty.
- 2. Fold wing in against the side of the unit and securely tie off. Then slowly tilt tank back onto its wheels.
- 3. Place seat in its "up" position and lock.
- 4. Insert hitch tongue and use both pins to secure it.
- 5. Attach trailer to vehicle. Put pin or bolt through hitch release lever and secure. Attach safety chain to vehicle.
- 6. Hook up lights to tow vehicle, and be sure to test the turn signals and brake lights before towing.
- 7. Place target, target arm, and tennis balls safely in tow vehicle.

#### PARTY MAGIC CONTRACT

DATE:

Client agrees to and shall indemnify and hold Party Magic, its employees and subcontractors harmless, from and against any and all claims, losses and damages if caused, directly or indirectly by the Client, its employees, guest, invitees, attendees or any person involved with or attending the event.

We are also not responsible for the guest and/or anyone the client directly hires who is not part of my contract and is therefore not under my auspices.

Proper instructions and/or directions are given at the time of the rental.

SIGNED	1.30	1/	
RENTAL	AGREEMENT #		 _